

Håndholdte Digital LCR Metre

ELC-133A 20000 Count Dual Display Digital LCR Meter, 10kHz

ELC-132A 20000 Count Dual Display Digital LCR Meter, 1kHz



ELC-132A / 133A

勝特力科技 886-3-5753170
百年電子 86-755-83289224
[Http://www.100y.com.tw](http://www.100y.com.tw)

Features

ELC-133A/132A

- Over-molded Case with Integrated Holster
- Large LCD with Dual Display and Backlight (ELC-133A)
- Resolution: 20,000 Count for L, C, R and 1,000 Count for D, Q, and q
- Measurement Parameters: R, L, C, D, Q, and q (q for ELC-133A only)
- Selectable Test Frequency : ELC-133A - 100Hz / 120Hz / 1kHz / 10kHz
ELC-132A - 120Hz / 1kHz
- Measurement Ranges :
L: 2mH to 1,000H; C: 2,000pF to 10mF; R: 20Ω to 10MΩ
Q: .000 to 999 Auto; D: .000 to 999 Auto; q: ± 90°
- Parallel and Serial Test Mode
- Auto and Manual Ranging
- 0.5% Basic Accuracy for Resistance Measurement
- 0.7% Basic Accuracy for Capacitance and Inductance Measurement
- Tolerance Mode: 1%, 5%, 10%, and 20%
- Max / Min / Avg Dynamic Recording
- Relative Mode for Reading Correlation and Comparison Applications
- Auto Protective Fuse Check
- Self-Calibration for Calibrating the Meter's Internal Parameters as well as External Connector Residuals
- Powered by Battery or External AC/DC Adapter
- Auto Power Off
- Low Battery Indicator
- Optical RS-232 Interface
- CE Mark