

ADAM-3900 Series

Wiring Terminals for
DIN-Rail Mounting



ADAM-3952

PCI-1240 50-Pin SCSI-II Wiring
Terminal for DIN-rail Mounting

Features

- DIN-rail mounting wiring terminal for PCI-1240 applications
- Case dimensions (W x L x H): 77.5 x 179.5 x 41.5mm (3.1" x 7.1" x 1.6")
- SCSI 50-pin connector
To be used with PCI-1240U and PCM-3240



NEW

ADAM-3952/J2S

PCI-1240 Wiring terminal for
Mitsubishi® MR-J2S

Features

- DIN-rail mounting wiring terminal for PCI-1240 connecting with Mitsubishi® MR-J2S servo motor driver
- Case dimensions (W x L x H): 121 x 202 x 45mm (4.76" x 7.95" x 1.77")
- One SCSI-100-pin connector to connect with PCI-1240/PCI-1240UU
- Eight SCSI 20-pin connector to connect with Mitsubishi motor driver
- Optional cable PCL-101100M-1 and PCL-10120M-2
To be used with PCI-1240U/PCM-3240



ADAM-3968M

PCI-1247 Wiring terminal

Features

- General purpose wiring terminal for PCI-1247 applications with DIN-rail mounting
- Case dimensions (W x L x H): 72 x 124 x 53 mm (2.83" x 4.88" x 2.09")
- One SCSI-68-pin connector to connect with PCI-1247
- Optional cable PCL-10168M-2



ADAM-3968M-PMA

PCI-1247 Wiring terminal for
Panasonic® Minas A Series

Features

- PCI-1247 wiring terminal for Panasonic® Minas A series driver with DIN-rail mounting
- Case dimensions (W x L x H): 72 x 124 x 53 mm (2.83" x 4.88" x 2.09")
- One SCSI-68-pin connector to connect with PCI-1247
- Two SCSI 50-pin connector to connect with Panasonic motor driver
- Optional cable PCL-10168M-2 and PCL-10150M-2




ADAM-3968M-J2S

PCI-1247 wiring terminal for
Mitsubishi MR-J2S series
driver

Features

- PCI-1247 wiring terminal for Mitsubishi® MR-J2S series driver with DIN-rail mounting
- Case dimensions (W x L x H): 72 x 124 x 53 mm (2.83" x 4.88" x 2.09")
- One SCSI-68-pin connector to connect with PCI-1247
- Four SCSI 20-pin connector to connect with Mitsubishi motor driver
- Optional cable PCL-10168M-2 and PCL-10120M-2



ADAM-3968M-YS2

PCI-1247 wiring terminal for
Yaskawa Sigma-II series
driver

Features

- PCI-1247 wiring terminal for Yaskawa® Sigma-II series driver with DIN-rail mounting
- Case dimensions (W x L x H): 72 x 124 x 53 mm (2.83" x 4.88" x 2.09")
- One SCSI-68-pin connector to connect with PCI-1247
- Two SCSI 50-pin connector to connect with Yaskawa motor driver
- Optional cable PCL-10168M-2 and PCL-10150M-2

1

Software

2

IPPC

3

TPC

4

FPM

5

ATM & AWS

6

DA&C

7

cPCI

8

ADAM-3000

9

Motion Control

10

ICOM

11

Industrial Networking

12

UNO

13

ADAM-4000

14

ADAM-5000

15

ADAM-6000

16

ADAM-8000


17

BAS

ADAM-3900 Series

Wiring Terminals for
DIN-Rail Mounting

NEW



ADAM-3941

PCI-1241/1242 Wiring Board
with LED

Features

- DIN-rail mounting wiring terminal for PCI-1241 and PCI-1242 applications
- Case dimensions (W x L x H): 169 x 112 x 51mm (6.7" x 4.4" x 2.0")
- SCSI 68-pin connector
- LED indicator

NEW



ADAM-3943

PCI-1243 Wiring Board with LED

Features

- DIN-rail mounting wiring terminal for PCI-1243U applications
- Case dimensions (W x L x H): 123 x 85 x 56mm (4.8" x 3.3" x 2.2")
- DB 62-pin female connector
- Tree-wire wiring for each channel

NEW



ADAM-3961

PCI-1261 Wiring Board with
LED

Features

- DIN-rail mounting wiring terminal for PCI-1261 applications
- Case dimensions (W x L x H): 169 x 112 x 51mm (6.7" x 4.4" x 2.0")
- SCSI 100-pin connector
- LED indicator

NEW



ADAM-3934D

Wiring board for ADAM-3750F
series

Features

- DIN-rail mounting wiring terminal for ADAM-3750F series applications
- Case dimensions (W x L x H): 123 x 85 x 56mm (4.8" x 3.3" x 2.2")
- 2 x 34-pin IDC male connector
- Tree-wire wiring for each channel

NEW



PCLD-8241

64 DI / 64 DO Remote IO Board

Features

- DIN-rail mounting wiring terminal for PCI-1241/1242/1261 applications
- Case dimensions (W x L x H): 292 x 112 x 56mm (11.5" x 4.4" x 2.2")
- D-sub 9-pin connector
- LED indicator